



CODE	JS	TS
φd 1	25.4	28.6
φd 2 ^{+0.15} / _{+0.02}	22.2	25.4
φD ^{+0.05} / ₀	27.0	30
S	1"x24	1-1/8"x26

L
150
180
210

技术部
 出图
 2014-12-17
 荣轮科技
 (深圳) 有限公司

NOTE: Custom steerers are threaded 40mm's

25	DUST SEAL	2	NBR		8	SPRING GUIDE	1	POM					
24	FIXING BOLT	1	STEEL		7	SPRING GUIDE	1	POM					
23	HOSE GUIDE	1	PA+GF33%	BLACK		MAIN SPRING (SOFT)	1	SWC	CHOICE				
22	TAPPING SCREW	2	STEEL			MAIN SPRING (HARD)	1	SWC					
21	BRACE COVER	1	PP		6	MAIN SPRING	1	SWC					
20	REMOTE SPEED LOCK ASSY	1			5	FORK PIPE L	1	STKM	CP, BR				
19	SUPPORT TUBE	1	PA66 GF30%		4	FORK PIPE R	1	STKM	CP, BR				
18	DAMPER UNIT	1	ALUMINUM		3	BOTTOM CASE	1	ALUMINUM	PAINTED				
17	BOTTOM STOPPER	1	PP		2	FORK CROWN TS, JS	1	AC4C-T6	BLACK OR BARREL				
16	FIXING NUT	2	STEEL		1	FORK STEM TS, JS	1	STKM					
15	NUT PLATE	1	SPC		NO.	DESCRIPTION	QTY.	MATERIAL	FINISH				
14	REBOUND SPACER	1	PP		MODEL				APP' D	SCALE			
13	REBOUND RUBBER	1	NBR		SF16-NEX-DS-RL-700C-50				CH' D	DATE			
12	FIXING BOLT	1	ALLOY STEEL		SR SUNTOUR INC.				DRAWN	DRAWN NO.			
11	ADJUSTER ASSY	1	GPPA	BLACK					Weizhiju				16. Dec. 2014
10	SLIDER SLEEVE	2	POM										SF-1410739
9	DAMPER	1	NBR										

30	STICKER	1	PETP	FOR H or S
29	FEATURE STICKER	1	PETP	
28	CAUTION STICKER	1	PETP	
27	MOUNT CAP	2	PE	
26	MOUNT CAP	2	PE	